

MIPG-24/HV Classic

– Multicolour Gelcoater



MIPG-24/HV Classic is a Multicolour Gelcoater with quick and simple changing of gelcoat colour. Overall, this technology offers numerous, cost-effective benefits such as high quality gelcoat finishes, ease of handling, low maintenance, safety and reliability with minimal

environmental impact. The Classic version has a static mixer on the machine, a pneumatically operated solvent pump for ease of cleaning and uses the same catalyst dosage technology that has made Applicator synonymous with quality products over the last decades.

MIPG-24/HV Classic

– Multicolour Gelcoater

OPERATION

Aplicator's MIPG-24/HV Classic machine uses air-driven dual-acting piston pumps for the gelcoats and the catalyst. For precise delivery of catalyst, regardless of variations in air supply or viscosity of material, the stainless-steel catalyst pump is synchronized with the gelcoat pump shaft. Catalyst volumes are easily adjusted by means of a hand wheel that changes the stroke length of the pump and the mixing ratios are continuously variable. The catalyst is pumped straight from the original container. Gelcoat is usually pumped from a 25-litre pail but can also be pumped from a 200-litre drum, a bulk container or a fixed storage tank. Using a static mixer, both catalyst and gelcoat are thoroughly blended before the material is pumped through a single hose to the gelcoat gun. For degassing and functional checks, the machine is equipped with a unique recirculation system for both catalyst and gelcoat.

CHANGE OF COLOUR AND INTERNAL MIXING

Aplicator have used internal mixing of gelcoat and catalyst for several years. This process has proved to be the optimum method of obviating problems that can occur with incomplete mixing. With MIPG-24/HV Classic it's quick and simple to change gelcoat colour without interrupting the production. Simply slide the air motor along the frame to a different gelcoat pump.

FLUSHING

Cleaning the spray gun after use is easily achieved using the built-in, pneumatically operated flushing pump. With no manual handling of potentially hazardous solvents, simply pressing the flush button on the pump automatically flushes the static mixer, hose and spray gun.

SPECIAL FEATURES

- Easy to operate
- Light weight spray gun
- Static mixer at machine
- Continuously adjustable catalyst ratio
- Flushing with solvent
- Pneumatic, push button, operated solvent pump
- Recirculation of gelcoat and catalyst
- Pumps can be added as needed
- Wheeled chassis for full mobility

TECHNICAL DATA

Air supply:	6 bar (90 psi)
Air consumption:	150 litres / litre output
Capacity:	Up to 6 litres / min, depending on viscosity, hose length/ diameter and nozzle orifice
Max. working pressure:	144 Bar (2169 psi)
Pressure ratio:	24:1
Mixing ratio:	Continuously variable between 0.8 and 4.0 %
Hose length:	Standard length 10 m
Weight of spray gun:	800 gr
Total weight:	Varies, dependent upon model

The machine showed on the overleaf might have extra equipment, modifications might have been made since the brochures were printed.



APLICATOR SYSTEM AB

Metallvägen 3
SE-435 33 Mölnlycke, Sweden
Telephone:+46 31 750 30 00
www.aplicatorgroup.com
info@aplicator.se

Branch offices; Aplicator System AB
Denmark info@aplicator.dk
Finland info@aplicator.fi
Spain info@aplicator.es
U.K info@aplicator.co.uk